

## Southwest Clean Air Agency State of Washington **Gasoline Cargo Annual** Certification

TANK OWNER:	TEST SITE:	
ADDRESS	ADDRESS	
CITY, STATE, ZIP	CITY, STATE, ZIP	
UNIT #:	TANK MFG:	
TEST DATE:	TANK SERIAL NO.	
TESTER:	TANK MFG DATE:	
DOT REG #:	TANK DOT SPEC:	
	Internal Vapor Valve Test – 40 CFR 63 42	25(e)(2)

After completing the pressure decay and vacuum tests, use the procedures in Method 27 to repressurize the tank to 18 inches H<sub>2</sub>O gauge. Close the tank's internal vapor valve(s), thereby isolating the vapor return line and manifold from the tank. Relieve all the pressure in the vapor return line to atmospheric pressure, then reseal the line. After 5 minutes, record the gauge pressure in the vapor return line.

	Initial Pressure (inches H <sub>2</sub> O)	Final Pressure (Inches H <sub>2</sub> O)	Pressure Increase
1 <sup>st</sup> test:	0"		
2 <sup>nd</sup> test (if repairs are necessary):	0"		

YES INO (check one) PASS:

Allowable Limit: 5 inches H2O

## Method 27 – 40 CFR Part 60, Appendix A

Pressure Decay Test - 40 CFR 63.425(e)(1) Conduct the test using a time period of 5 minutes. The initial pressure shall be 18 inches H<sub>2</sub>O gauge.

	Capacity	Initial Pressure	Final Pressure	Pressure
	(gallons)	(inches H <sub>2</sub> O)	(Inches H <sub>2</sub> O)	Decay
1 <sup>st</sup> test:		18"		
2 <sup>nd</sup> test:		18"		
3 <sup>rd</sup> test (if repairs are necessary):		18"		
Average of the 2 tests with pressure decay within 0.5 inches H <sub>2</sub> O of each other				

PASS: YES INO (check one)

Vacuum Decay Test - 40 CFR 63.425(e)(1) Conduct the test using a time period of 5 minutes. The initial vacuum shall be 6 inches  $H_2O$  gauge.

	Capacity (gallons)	Initial Vacuum (inches H <sub>2</sub> O)	Final Vacuum (Inches H <sub>2</sub> O)	Vacuum Decay
1 <sup>st</sup> test:		6"		
2 <sup>nd</sup> test:		6"		
3 <sup>rd</sup> test (if repairs are necessary):		6"		
Average of the 2 tests with pressure decay within 0.5 inches H <sub>2</sub> O of each other				

PASS: YES INO (check one)

Allowable Limits	Capacity (gal)	Decay		
for both tests:	> 2,499	1.0"		
	1,500 to 2,499	1.5"		
	1,499 to 1,000	2.0"		
	< 1,000	2.5"		

Vapor tightness repair (if any) – nature of repair work and when performed in relation to the test:

	<u>Compa</u> <u>Size</u>	<u>1</u> rtment	2	<u>3</u>	<u>4</u>	<u>5</u>
		Certi	fication N	0		
		Expir	ation Dat	e:		
		Date	Paid:			
Signature of Tester:	Date:	Recei	pt No			