

Southwest Clean Air Agency

11815 NE 99th Street, Suite 1294 • Vancouver, WA 98682-2322 (360) 574-3058 • Fax: (360) 576-0925 www.swcleanair.org

July 22, 2011

Diana M. Gritten-MacDonald Manager Environmental and Regulatory Services Cowlitz County PUD 961 12th Avenue PO Box 3007 Longview, WA 98632

Subject:

Notification of Emergency Generator Set Installation

Dear Ms. Gritten-MacDonald:

The Southwest Clean Air Agency (SWCAA) received your small unit notification (SUN) for the Cowlitz PUD's main office at 961 12th Avenue, Longview, Washington on July 13, 2011. For administrative and tracking purposes SWCAA has assigned tracking number SUN-004 to this notification. This notification was filed in accordance with SWCAA 400-072 and applies to the installation of one emergency service internal combustion engine. The new engine is identified as follows:

(1) 755 bhp (standby) diesel-fired Cummins model QSX15-G9 engine to drive a 500 kW (standby) generator set. The engine will be EPA Tier 2 certified. The generator set is a Cummins model 500DFEK.

SWCAA has completed a review of your notification and the associated support information and has determined that it is sufficient as per the requirements of SWCAA 400-072(2). Once installed, affected equipment must maintain compliance with the requirements of SWCAA 400-072(4)(c) "Emergency service internal combustion engines". A copy of the relevant SWCAA 400-072 section is attached for your information.

Be advised that emission units installed pursuant to SWCAA 400-072 are subject to source registration and periodic inspection. Registration fees for this equipment will be invoiced consistent with SWCAA 400-100.

If you need further assistance or have any questions regarding these matters, please contact me at (360) 574-3058 extension 130.

Sincerely,

Paul T. Mairose

Daul Manore

Chief Engineer

SWCAA 400-072 Emission Standards for Selected Small Source Categories

[Statutory Authority: Chapter 70.94.141 RCW. Original adoption 09-21-056 filed 10/15/09, effective 11/15/09.]

(4) Source categories.

- (c) Emergency service internal combustion engines.
 - (i) **Applicability.** The provisions of this section apply to emergency service internal combustion engines with a rating of less than 1,000 horsepower (e.g., emergency generators, fire pumps, sewer lift stations, etc.).
 - (ii) Emission limits and standards.
 - (A) Visible emissions from diesel fired engine exhaust stacks shall not exceed ten percent opacity for more than 3 minutes in any one hour period as determined in accordance with SWCAA Method 9 (See SWCAA 400, Appendix A). This limitation shall not apply during periods of cold start-up.

(iii) General requirements.

- (A) Liquid fueled engines shall only be fired on #2 diesel or biodiesel. Fuel sulfur content of liquid fuels shall not exceed 0.0015% by weight (15 ppmw). A fuel certification from the fuel supplier may be used to demonstrate compliance with this requirement.
- (B) Gaseous fueled engines shall only be fired on natural gas or propane.
- (C) Each compression ignition engine shall be EPA Tier certified and manufactured no earlier than January 1, 2008.
- (D) Engine operation shall be limited to maintenance checks, readiness testing, and actual emergency use.
- (E) Engine operation for maintenance checks and readiness testing shall not exceed 100 hours per year. Total engine operation shall not exceed 200 hours per year.
- (F) Each engine shall be equipped with a nonresettable hourmeter for the purpose of documenting hours of operation.
- (G) Engine exhaust shall be discharged vertically. Any device that obstructs or prevents vertical discharge is prohibited.
- (iv) Monitoring and recordkeeping requirements. The information listed below shall be recorded at the specified intervals, and maintained in a readily accessible form for a minimum of 3 years. With the exception of data logged by a computerized data acquisition system, each required record shall include the date and the name of the person making the record entry.
 - (A) Total hours of operation for each engine shall be recorded annually;
 - (B) Fuel sulfur certifications shall be recorded for each shipment of liquid fuel;
 - (C) Maintenance activities shall be recorded for each occurrence consistent with the provisions of 40 CFR 60.4214;
 - (D) Upset conditions that cause excess emissions shall be recorded for each occurrence; and
 - (E) All air quality related complaints received by the permittee and the results of any subsequent investigation or corrective action shall be recorded for each occurrence.
- (v) **Testing requirements.** None.

(vi) Reporting requirements.

- (A) All air quality related complaints received by the owner or operator shall be reported to SWCAA within three calendar days of receipt.
- (B) The owner or operator of an affected emergency engine shall report the following information to the Agency no later than March 15th for the preceding calendar year:
 - (I) Hours of engine operation; and
 - (II) Air emissions of criteria air pollutants, VOCs, and toxic air pollutants (TAPs).